THE POWER COMPANY

TECHNICAL DATA SHEET

Banner
THE POWER COMPANY

GENERAL DATA

Typ:	6 PzF 72
Product Group:	Traction Bull Bloc Nass
Article Number:	040500720612

DIMENSIONS AND WEIGHTS

Max. length (mm):	352
Max. width (mm):	175
Max. total height (mm):	190
Battery weight filled (kg +/- 5%):	23
Electrolyte density (kg/litre +/- 0,01kg/l. at 25 °C):	1,28
Elektrolyte:	diluted sulfuric acid

ELECTRICAL DATA

Rated voltage (V):	12
Rated capacity K5 (Ah):	72
Rated capacity K20 (Ah):	96
Self discharge:	approx. . 1,5% month

EXECUTION

Container and cover:	PP
Handle:	yes
Torque setting (Nm):	8
Delivery condition:	filled and charged
Plugs:	thread M15
Terminal position:	0
Terminal type:	AP automotive post
Separator:	Polyäthylen
Plates:	positive tubular plate, negative grid plate
Degassing:	degassing by plugs

MAINTENANCE

Maintenance Interval:	weekly
Check of electrolyte level:	possible
Water for refill:	distilled and demineralized
Gassing voltage (V):	approx. 14,4
Charging current (A):	approx. 12
Charging final voltage (V):	approx. 16,2
Discharge final voltage (V at 80% depth of discharge):	approx. 11,10

The specified electrical values apply to loads in a fully charged state and an ambient temperature of 20°C.
All dimension and weight specifications are subject to standard manufacturing tolerances.

Banner GmbH, A-4600 Thalheim bei Wels, Am Thalbach 21
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com

LEADING COMPANIES OF AUSTRIA

POLE EXECUTION

Banner GmbH, A-4600 Thalheim bei Wels, Am Thalbach 21
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com

LEADING COMPANIES OF AUSTRIA