THE POWER COMPANY

TECHNICAL DATA SHEET



GENERAL DATA

Typ:	DB 60 FT
Product Group:	Traction Bull Bloc Gel
Article Number:	04051060FT

ELECTRICAL VALUES

Rated voltage (V):	12
Rated capacity K5 (Ah):	47,4
Rated capacity K20 (Ah):	60
Self discharge:	very low

EXECUTION

Container and cover:	PP Polypropylen
Handle:	no
Torque setting (Nm):	6
Delivery condition:	filled and charged
Plugs:	none; valves must NOT be opened
Terminal position:	0
Terminal type:	FT 6,35mm flat terminal
Separator:	special separator with glass mat
Plates:	positive and negative grid plates, lead-calcium alloy
Degassing:	Pressure Relief Valve, VRLA

DIMENSIONS AND WEIGHTS

Max. length (mm):	259
Max. width (mm):	169
Max. total height (mm):	178
Battery weight filled (kg +/- 5%):	17,7
Elektrolyte:	bounded in Gel

MAINTENANCE

Maintenance Interval:	maintenance-free; no maintenance required
Check of electrolyte level:	no possible
Charging current (A):	11
Charging final voltage (V):	approx. 15 (voltage-regulated charging only)
Discharge final voltage (V at 70% depth of discharge):	11,10


The specified electrical values apply to loads in a fully charged state and an ambient temperature of 20°C.
All dimension and weight specifications are subject to standard manufacturing tolerances.

bannerbatterien.com

Banner GmbH, A-4600 Thalheim bei Wels, Am Thalbach 21
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com

LEADING COMPANIES OF AUSTRIA

POLE CONFIGURATION



Gewinde = ¼ Zoll

Banner GmbH, A-4600 Thalheim bei Wels, Am Thalbach 21
Tel. +43(0) 732/38 88-0, e-mail: internet@bannerbatterien.com
LEADING COMPANIES OF AUSTRIA