



ELECTRICAL VALUES

Rated voltage (V):	12
Rated capacity K5 (Ah):	105
Rated capacity K20 (Ah):	120
Self discharge:	very low

EXECUTION

Container and cover:	ABS Acrylbutadienstyrol
Handle:	yes
Torque setting (Nm):	8
Delivery condition:	filled and charged
Plugs:	none; valves must NOT be opened
Terminal position:	0
Terminal type:	AP automotive post
Separator:	special separator with glass mat
Plates:	positive and negative grid plates, lead-calcium alloy
Degassing:	Pressure Relief Valve, VRLA

GENERAL DATA

Typ:	DB 120
Product Group:	Traction Bull Bloc Gel
Article Number:	04051DB120



DIMENSIONS AND WEIGHTS

Max. length (mm):	329
Max. width (mm):	170
Max. total height (mm):	282
Battery weight filled (kg +/- 5%):	42
Electrolyte:	bounded in Gel

MAINTENANCE

Maintenance Interval:	maintenance-free; no maintenance required
Check of electrolyte level:	no possible
Charging current (A):	I = min. 12% C5, max. 18% C5
Charging final voltage (V):	approx. 15 (voltage-regulated charging only)
Discharge final voltage (V at 70% depth of discharge):	11,10

The specified electrical values apply to loads in a fully charged state and an ambient temperature of 20°C.
All dimension and weight specifications are subject to standard manufacturing tolerances.

POLE CONFIGURATION

